


AUFHÄNGEKOPF, einsträngig, Edelstahl, 1.4404
 ohne Flachstelle, Güteklasse 6, EN 818-2



Bestell-Nr.	Tragfähigkeit [t]	Ketten-Ø		Abmessungen			Gewicht ca. [kg]
		1-str. [mm]	2-str. [mm]	d [mm]	b [mm]	t [mm]	
25050008	0,40	4	-	8	30	54	0,07
25050010	0,63	5	4	10	50	80	0,15
25050013	1,55	6/7/8	5/6	13	60	110	0,34
25050016	2,45	10	7/8	16	60	110	0,53
25050018	3,55	-	10	18	75	135	0,80
25050022	6,00	13/16	13	22	90	160	1,50
25050026	8,00	18	16	26	100	180	2,30
25050032	12,00	20	18	32	110	200	3,90
25050036	16,00	-	20	36	140	260	6,35



B-Aufhängekopf

25050060	0,40	-	-	5	9	22	0,01
25050061	0,63	-	-	6	13	26	0,02
25050062	1,25	-	-	8	19	35	0,05
25050063	1,55	-	-	10	25	44	0,09
25050064	2,45	-	-	13	25	54	0,20
25050065	3,85	-	-	16	34	70	0,37
25050066	6,00	-	-	18	40	85	0,53
25050067	7,60	-	-	22	50	115	1,07
25050068	9,60	-	-	26	65	140	1,83

Aufhängeköpfe lieferbar für Kranhaken bis 50 t.

NEUMANN GMBH Hebesysteme Fördertechnik	Paul-Ehrlich-Straße 5a 63128 Dietzenbach	Tel. 06074 8504-0 Fax 06074 850412	E-Mail info@neumann-gmbh.com www.neumann-gmbh.com
--	---	---------------------------------------	---