


Vollkauschen DIN 3091 mit Rohbohrung, roh + verzinkt

Material: 8-18 mm GTW-40 DIN 1692
20-80 mm GGG-40 DIN 1693

Bestell-Nr.	Bestell-Nr.	für Seil-Ø	Abmessungen		Rohmaß d1	Fertigmaß d1	Abmessungen		Gewicht ca.
			a	b			c	l	
roh	verzinkt	[mm]	[mm]	[mm]	[mm]	max. [mm]	[mm]	[mm]	[kg]
22390001	22390051	8	9	15	14	20	40	66	0,18
22390002	22390052	10	11	18	18	25	50	82	0,32
22390003	22390053	12	13	20	21	30	60	98	0,51
22390004	22390054	14	16	24	25	35	70	114	0,80
22390005	22390055	16	18	26	28	40	80	130	0,90
22390006	22390056	18	20	29	31	45	90	145	1,21
22390007	22390057	20	22	31	35	50	100	161	1,61
22390008	22390058	22	24	34	38	55	110	177	2,11
22390009	22390059	24	26	36	41	60	120	193	2,71
22390010	22390060	26	29	40	44	65	130	209	3,55
22390011	22390061	28	31	42	47	70	140	224	4,20
22390012	22390062	32	35	47	53	80	160	256	6,30
22390013	22390063	36	40	53	59	90	180	288	8,84
22390014	22390064	40	44	58	65	100	200	320	11,00
22390015	22390065	44	48	63	70	110	220	352	15,00
22390016	22390066	48	53	69	76	120	240	384	20,00
22390017	22390067	52	57	74	81	130	260	416	25,00
22390018	22390068	56	62	80	86	140	280	448	32,00
22390019	22390069	64	70	90	95	160	320	512	46,00
22390020	22390070	72	79	101	104	180	360	576	66,00
22390021	22390071	80	88	112	112	200	400	640	90,00



NEUMANN GMBH	Paul-Ehrlich-Straße 5a	Tel. 06074 8504-0	E-Mail info@neumann-gmbh.com
Hebesysteme Fördertechnik	63128 Dietzenbach	Fax 06074 850412	www.neumann-gmbh.com